


Curva SS SR 90°

Norme: ASME B16.9 – ASTM403

Materiale: Aisi 304L EN 1.4307 – Aisi 316L EN 1.4404

cod. 303-SR



De x Spessore mm	Dimensioni	R mm	Stock	Peso kg
33,40 x 2,77	1" SCH 10S	25	R	0,10
33,40 x 3,38	1" SCH 40S	25	D	0,12
33,40 x 4,55	1" SCH 80S	25	R	0,13
42,16 x 2,77	1.1/4" SCH 10S	32	R	0,15
42,16 x 3,56	1.1/4" SCH 40S	32	D	0,20
42,16 x 4,85	1.1/4" SCH 80S	32	R	0,22
48,26 x 2,77	1.1/2" SCH 10S	38	R	0,22
48,26 x 3,68	1.1/2" SCH 40S	38	D	0,29
48,26 x 5,08	1.1/2" SCH 80S	38	R	0,32
60,33 x 2,77	2" SCH 10S	51	R	0,37
60,33 x 3,91	2" SCH 40S	51	D	0,51
60,33 x 5,54	2" SCH 80S	51	R	0,60
73,03 x 3,05	2.1/2" SCH 10S	64	R	0,62
73,03 x 5,16	2.1/2" SCH 40S	64	D	1,02
73,03 x 7,01	2.1/2" SCH 80S	64	R	1,14
88,90 x 3,05	3" SCH 10S	76	R	0,90
88,90 x 5,49	3" SCH 40S	76	D	1,50
88,90 x 7,62	3" SCH 80S	76	R	1,85
114,30 x 3,05	4" SCH 10S	102	R	1,72
114,30 x 6,02	4" SCH 40S	102	D	3,12
114,30 x 8,56	4" SCH 80S	102	R	3,05
141,30 x 3,40	5" SCH 10S	127	R	2,75
141,30 x 6,55	5" SCH 40S	127	R	5,28
168,28 x 3,40	6" SCH 10S	152	D	4,15
168,28 x 7,11	6" SCH 40S	152	R	7,15
168,28 x 10,97	6" SCH 80S	152	R	11,79
219,08 x 3,76	8" SCH 10S	203	R	8,00
219,08 x 8,18	8" SCH 40S	203	R	17,05
273,05 x 4,19	10" SCH 10S	254	R	12,40
273,05 x 9,27	10" SCH 40S	254	R	24,00
323,85 x 4,57	12" SCH 10S	305	R	17,20
323,85 x 9,53	12" SCH 40S	305	R	38,10
355,60 x 4,78	14" SCH 10S	406	R	23,09
355,60 x 9,52	14" SCH 40S	406	R	45,40
406,40 x 4,78	16" SCH 10S	457	R	30,84