


Curva SS LR 90°

Norme: ASME B16.9 – ASTM403

Materiale: Aisi 304L EN 1.4307 - Aisi 316L EN 1.4404

cod. 303



De x Spessore mm	Dimensioni	R mm	Stock	Peso kg
21,34 x 2,11	1/2" SCH 10S	38	D	0,06
21,34 x 2,77	1/2" SCH 40S	38	D	0,08
21,34 x 3,73	1/2" SCH 80S	38	R	0,10
26,67 x 2,11	3/4" SCH 10S	38	D	0,07
26,67 x 2,87	3/4" SCH 40S	38	D	0,09
26,67 x 3,91	3/4" SCH 80S	38	R	0,11
33,40 x 2,77	1" SCH 10S	38	D	0,14
33,40 x 3,38	1" SCH 40S	38	D	0,16
33,40 x 4,55	1" SCH 80S	38	R	0,22
42,16 x 2,77	1.1/4" SCH 10S	48	D	0,23
42,16 x 3,56	1.1/4" SCH 40S	48	D	0,25
42,16 x 4,85	1.1/4" SCH 80S	48	R	0,40
48,26 x 2,77	1.1/2" SCH 10S	57	D	0,30
48,26 x 3,68	1.1/2" SCH 40S	57	D	0,40
48,26 x 5,08	1.1/2" SCH 80S	57	R	0,51
60,33 x 2,77	2" SCH 10S	76	D	0,51
60,33 x 3,91	2" SCH 40S	76	D	0,71
60,33 x 5,54	2" SCH 80S	76	R	0,91
73,03 x 3,05	2.1/2" SCH 10S	95	D	0,85
73,03 x 5,16	2.1/2" SCH 40S	95	D	1,36
73,03 x 7,01	2.1/2" SCH 80S	95	R	1,81
88,90 x 3,05	3" SCH 10S	114	D	1,22
88,90 x 5,49	3" SCH 40S	114	D	2,18
88,90 x 7,62	3" SCH 80S	114	R	2,98
114,30 x 3,05	4" SCH 10S	152	D	2,15
114,30 x 6,02	4" SCH 40S	152	D	4,17
114,30 x 8,56	4" SCH 80S	152	R	6,18
141,30 x 3,40	5" SCH 10S	190	D	3,63
141,30 x 6,55	5" SCH 40S	190	D	6,86
141,30 x 9,53	5" SCH 80S	190	R	9,58
168,28 x 3,40	6" SCH 10S	229	D	4,90
168,28 x 7,11	6" SCH 40S	229	D	10,90
168,28 x 10,97	6" SCH 80S	229	R	16,33
219,08 x 3,76	8" SCH 10S	305	D	10,66
219,08 x 8,18	8" SCH 40S	305	D	21,50
219,08 x 12,70	8" SCH 80S	305	R	33,11
273,05 x 4,19	10" SCH 10S	381	R	19,50
273,05 x 9,27	10" SCH 40S	381	R	38,60
323,85 x 4,57	12" SCH 10S	457	R	27,22
323,85 x 9,53	12" SCH 40S	457	R	59,40
355,60 x 4,78	14" SCH 10S	533	R	36,30
355,60 x 9,53	14" SCH 40S	533	R	70,30
406,40 x 4,78	16" SCH 10S	610	R	47,63
406,40 x 9,53	16" SCH 40S	610	R	91,60
457,20 x 4,78	18" SCH 10S	686	R	59,87
457,20 x 9,53	18" SCH 40S	686	R	113,00
508,00 x 5,54	20" SCH 10S	762	R	99,79
508,00 x 9,52	20" SCH 40S	762	R	140,00
609,60 x 6,35	24" SCH 10S	914	R	140,61
609,60 x 9,52	24" SCH 40S	914	R	207,80