


# Curva SS LR 45°

Norme: ASME B16.9 – ASTM403

Materiale: Aisi 304L EN 1.4307 – Aisi 316L EN 1.4404

cod. 307



De x Spessore mm	Dimensioni	R mm	Stock	Peso kg
21,34 x 2,11	1/2" SCH 10S	38	R	0,03
21,34 x 2,77	1/2" SCH 40S	38	R	0,04
26,67 x 2,11	3/4" SCH 10S	38	R	0,03
26,67 x 2,87	3/4" SCH 40S	38	R	0,05
33,40 x 2,77	1" SCH 10S	38	R	0,07
33,40 x 3,38	1" SCH 40S	38	R	0,08
42,16 x 2,77	1.1/4" SCH 10S	48	R	0,12
42,16 x 3,56	1.1/4" SCH 40S	48	R	0,14
48,26 x 2,77	1.1/2" SCH 10S	57	R	0,15
48,26 x 3,68	1.1/2" SCH 40S	57	R	0,20
60,33 x 2,77	2" SCH 10S	76	R	0,26
60,33 x 3,91	2" SCH 40S	76	R	0,36
73,03 x 3,05	2.1/2" SCH 10S	95	R	0,42
73,03 x 5,16	2.1/2" SCH 40S	95	R	0,68
88,90 x 3,05	3" SCH 10S	114	R	0,61
88,90 x 5,49	3" SCH 40S	114	R	1,09
114,30 x 3,05	4" SCH 10S	152	R	1,08
114,30 x 6,02	4" SCH 40S	152	R	2,09
141,30 x 3,40	5" SCH 10S	190	R	1,81
141,30 x 6,55	5" SCH 40S	190	R	10,75
168,28 x 3,40	6" SCH 10S	229	R	2,45
168,28 x 7,11	6" SCH 40S	229	R	5,45
219,08 x 3,76	8" SCH 10S	305	R	5,33
219,08 x 8,18	8" SCH 40S	305	R	16,55