


# Curva 45° Long Radius Welded

Norme: ASME B16.9 – ASTM A403 WP-W

Materiale: Aisi 304L EN 1.4307 – Aisi 316L EN 1.4404

cod. 307W



De x Spessore mm	Dimensioni	R mm	Stock	Peso kg
88,90 x 3,05	3" SCH 10S	114	R	0,61
88,90 x 5,49	3" SCH 40S	114	R	1,09
114,30 x 3,05	4" SCH 10S	152	R	1,08
114,30 x 6,02	4" SCH 40S	152	R	2,09
141,30 x 3,40	5" SCH 10S	190	R	1,81
141,30 x 6,55	5" SCH 40S	190	R	10,75
168,28 x 3,40	6" SCH 10S	229	R	2,45
168,28 x 7,11	6" SCH 40S	229	R	5,45
219,08 x 3,76	8" SCH 10S	305	R	5,33
219,08 x 8,18	8" SCH 40S	305	R	16,55
273,05 x 4,19	10" SCH 10S	381	R	8,30
273,05 x 9,27	10" SCH 40S	381	R	19,30
323,85 x 4,57	12" SCH 10S	457	R	14
323,85 x 9,53	12" SCH 40S	457	R	27
355,6 x 4,78	14" SCH 10S	533	R	14
355,6 x 9,53	14" SCH 40S	533	R	37
406,4 x 4,78	16" SCH 10S	609	R	24
406,4 x 9,53	16" SCH 40S	609	R	48,5